



C35200 – DZR MACHINING BRASS

EQUIVALENT SPECIFICATION

Grade: C35200 / DZR Brass
Standard: Australia Standard

CHEMICAL SPECIFICATION

Cu	Pb	Fe	Zn	Imp.	Sn	Ni	Al	As	
61.5–63.5	0.2	0.1	Rem	0.2	0.1	0.3	0.05	0.02–0.15	

DESCRIPTION:

Jalaram Metal Alloys – Alloy C35200 Brass is a copper-zinc-lead alloy with a small addition of arsenic, having a mainly alpha phase structure in the "as used" heat treated condition, with a fine dispersion of lead particles. It has excellent machinability, good cold forming properties, with a high resistance to dezincification.

TYPICAL APPLICATIONS:

Plumbing Fittings.

PRODUCT

Rods & Bars
Hollow
Sections & Profiles
Ingots
Billets

SIZE RANGE

Dia. 8.00 mm to 101.00 mm

OTHER ALLOYS

Free Cutting Brass
Forging Brass
Naval Brass
Leaded Brass

Lead Free Brass
Silicon Brass
Eco Brass
DZR Brass

Low Leaded Brass
High tensile Brass
Bismuth Bronze
Copper & Copper Alloys



CONTACT US AT



sales@jalarammetalalloys.com



Plot No. 5, Survey No. 202,
Near G.I.D.C. Phase-3 (Kansumra),
Jamnagar-361006, Gujarat, INDIA

NIKET SHAH

+91 9879 234 953
+91 9825 124 243