



CuZn40 (C28000) – Muntz Metal

EQUIVALENT SPECIFICATION

Grade: CuZn40 (C28000)

Standard: ASTM B 36

CHEMICAL SPECIFICATION

Cu	Pb	Fe	Zn						
59 - 63	0.1	0.07	Rem						

DESCRIPTION:

Jalaram Metal Alloys - C28000 Muntz Metal, also known as 60/40, is copper alloyed with zinc. C280 Muntz is most commonly found in sheet and plate form. CuZn40 is considered a duplex alpha-plus-beta brass and has excellent hot-working properties but is less corrosion resistant than C464 Naval Brass. C28000 Muntz is commonly used in architectural applications, including decorative panels, elevators, trim work and signage. Compared to the yellow tones of C260 Cartridge Brass, C280 Muntz has a warmer appearance that readily takes to polishing.

TYPICAL APPLICATIONS:

Decoration, Architectural Panels, Hardware, Door Frames, Large Architectural Trim, Structural, Heavy Plate, Sheet, Large Sheets. Builders Hardware, Fasteners, Condenser Tube, Valve Stems, Hot Forgings, Heat Exchanger Tube, Large Nuts & Bolts, Evaporator Tubes, Brazing Rod, Condenser Plates. Locks & metal fittings, Keys.

PRODUCT

Rods & Bars
Hollow
Sections & Profiles
Ingots
Billets

SIZE RANGE

Dia. 8.00 mm to 101.00 mm

OTHER ALLOYS

Free Cutting Brass
Forging Brass
Naval Brass
Leaded Brass

Lead Free Brass
Silicon Brass
Eco Brass
DZR Brass

Low Leaded Brass
High tensile Brass
Bismuth Bronze
Copper & Copper Alloys



CONTACT US AT



sales@jalarammetalalloys.com



Plot No. 457, G.I.D.C. Shankar Tekri
Udyognagar, Jamnagar-361004,
Gujarat, INDIA

NIKET SHAH

+91 9879 234 953
+91 9825 124 243